

**PUREZZA™**

PREMIUM WATER

# P2 Firewall™ Bar Classe Series

Unparalleled dispensing and purification performance in an elegantly designed unit



The P2 Firewall Bar Classe Series is a robust, reliable and sophisticated dispenser providing unlimited, purified ice-cold still and sparkling water. The unit has been designed with HoReCa environments in mind, where high output and high flow are in demand.

The visual appeal of the P2 Firewall Bar Classe Series complements any hospitality environment.

## Leading technology



### Performance filtration

Professional grade filters are used to satisfy the need for high water consumption, addressing colour, taste and odour, for great tasting, crystal-clear water.



### Firewall purification

High flow Firewall UVC purification thoroughly purifies the water up to the point of dispense, for microbiologically safe water. Guaranteed to remove up to 99.9999% bacteria, 99.99% viruses and 99.9% cysts. Certified by IAPMO R&T to NSF 55 Class A and P231 standards for microbiological water purifiers.



### Ice Bath cooling technology

The Ice Bath water cooling system delivers high volumes of ice-cold water, catering for environments where such a need is paramount.



### BioCote® antimicrobial protection

The bottle holders and floater mechanism are protected by BioCote® antimicrobial technology proven effective against all common microbes including bacteria, mould and fungi.



## Features

NSF 55 Class A and NSF P231 certified Firewall, patented UVC technology, deactivates most viruses, cysts and pathogenic bacteria, thoroughly purifying the water up to 99.9999%

Firewall UV lamp monitoring system guarantees consistent standards of water purification

Ice Bath cooling technology for abundance of highly purified still and sparkling ice-cold water

Sparkling system includes CO<sub>2</sub> gas pressure control and is engineered to deliver supreme quality ice-cold effervescent water, comparable to even the finest bottled water

Electronic push dispense buttons allow for continuous dispense (max 3 litres) or pre-set portion control to fill 750 ml and 1 litre size bottles. Sequential dispense (one pre-set dispense after the other from each tap) can also be set up for peak-time usage

The ergonomic dispense area and the adjustable height drip tray are designed to accommodate various size vessels

Clearly visible dispense nozzles and circular bottle holders allow for accurate positioning of the bottles, preventing displacement and unnecessary water spillage


Removable steel side plate facilitates air filter cleaning operations

LED side panel displays filter, Firewall and Ice Bath fault indicators, as well as other system diagnostics for optimum service efficiency and peace of mind

Programmable energy saving sleep mode to significantly reduce power consumption when the unit is not in use

## Water options

cold      sparkling



## Tested and certified



The HORECA Firewall is certified by IAPMO R&T to NSF/ANSI 55 Class A, NSF P231, and US EPA Guide Standard and Protocol for Testing Microbiological Water Purifiers, NSF 372 for lead free compliance and Watermark Australia.



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Purezza and the Purezza logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Technical specifications

### Types available

Countertop and freestanding (with optional base cabinet) [Both available on request with hands-free pedal operations.]

### Dimensions

Countertop (including wheels):  
400 mm (W) x 607 mm (H) x 590 mm (D)  
Freestanding:  
400 mm (W) x 1392 mm (H) x 590 mm (D)

### Dispense area height

22 cm-32 cm (adjustable)

### Weight

Countertop: Net 48 kg  
Base cabinet: Net 21.2 kg

### Filtration\*

High performance carbon filter  
\*Filter type depending on local water conditions

### Storage capacity

Ice bath: 21 litres  
Sparkling tank: 1 litre

### Dispensing capacity

Up to 160L/h

### Flow rate

2.5-3.5 litre/min

### Compressor

AU compressor (R600a): 210W

### Water temperature output

Cold: 3-12 °C  
Sparkling: 3-12 °C

Contact the Purezza team today

### Purezza Australia

1300 88 14 14  
sales@purezza.com.au

For more information, visit [www.purezza.com.au](http://www.purezza.com.au)